

HEKTO SCREENING

Audiometer



AUDIOMETER SCREENING VERSION

HEKTO SCREENING is one of the three versions of portable PC-based audiometer produced by HORENTEK®, also in this version there are 2 channels, it is designed for specialists who need a basic device, but accurate in examinations and with reduced dimensions, practical and portable, especially dedicated to occupational medicine. It is perfect for those who are used to do audiometric tests outside their clinic.

HEKTO screening can perform the following tests: Air conduction Pure tone Audiometry (PTA), Audiometry in Free field and Hughson-Westlake automatic audiometry.

TECHNICAL DATA

Frequency Range	AC from 125Hz to 8KHz
Dynamic Range (1000 Hz)	from -10dB HL to 120dB HL
Digital to Analogic Conversion	2 independent channels
Aux Input	CD-ROM
Weight	250 g
Dimension	170 x 95 x 25 mm
AC (Tonal Audiometry)	•
BC (Tonal Audiometry)	-
Masking (White Noise, Narrow Band Noise Masking)	•
Free Field	•
Automatic HW Audiometry	•
MCL (Most Comfortable Level)	•
UCL (Un Comfortable Level)	•
Speech Test	-
Special Test (ABLB, SISI, Bekesy and Tone Decay)	-
HF Audiometry	-
Tinnitus Assestment	-